

POLYFLOR CAMARO WOOD PU

- Camaro - collection of versatile vinyl floor products
- Wood effect floorcovering designs
- Coordinating grouting, marquetry and feature strips are readily available to blend, shape or accentuate design ideas

SPECIFICATION



2.0mm



0.3mm



36 @ 101 x 914mm = 3.34m²
 24 @ 152 x 914mm = 3.34m²
 18 @ 152 x 1219mm = 3.34m²
 14 @ 203 x 1219mm = 3.46m²



3600g/m²

LUXURY VINYL
TILES



CAMARO™
FLOORING COLLECTION

WOOD P₁



GENERAL PERFORMANCE

EN 649

F1303-99 Type I Grade 2



REACTION TO FIRE

EN ISO 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
 EN ISO 11925-2 Pass



SLIP RESISTANCE

EN 13893 Class DS (dry condition)*
 AS/NZS 4586 R9



LIGHT FASTNESS

ISO 105-B02 Method 3 ≥6



ABRASION RESISTANCE

EN 649 Group T



ELECTRICAL BEHAVIOUR (body voltage)

EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



INDENTATION - RESIDUAL

EN 433 ≤ 0.1mm



DIMENSIONAL STABILITY

EN 434 ≤ 0.25%



CASTOR CHAIR (continuous use)

Suitable



THERMAL CONDUCTIVITY

Suitable for underfloor heating Max. 27°C



ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Camaro PU achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429) in major use areas such as retail. Camaro PU is 100% recyclable and contains 15% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



APPLICATIONS

Polyflor Camaro PU is suitable for use in any domestic situation and moderate commercial areas such as offices, hotels and boutiques.




For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

PERFORMANCE AND PROPERTIES



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
 WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2006

January 2011

POLYFLOR™
COVERING THE WORLD